





HIGHLIGHTS

Rugged all-metal body and robust design

withstands tough day-to-day use

Switchable bass-cut filter

eliminates rumble or footfall noise

Switchable attenuation pad

for high SPL applications up to 150 dB dB SPL

KEY MESSAGE

The P120 is a 2/3-inch diaphragm true condenser microphone that offers solidly built quality, outstanding performance and excellent value. The low-mass diaphragm delivers a clear sound with accurate sonic detail for vocals, speech and instrument recording in project studios and for home recording.

P120



HIGH-PERFORMANCE GENERAL PURPOSE RECORDING MICROPHONE

APPLICATIONS

PROJECT STUDIOS HOME RECORDINGS STAGE

TECHNICAL SPECIFICATIONS

Audio frequency bandwidth:20 to 20000 HzEquivalent noise level:19 dB-ASensitivity:24 mV/PaSignal to Noise:75 dB-APreattenuation Pad:-20 dB

Bass Cut Filter:300 -6 dB/octave HzElectrical Impedance:≤200 OhmsRecommended load impedance:≥1000 OhmsPolar Patterns:Cardioid

Audio Output

Type: Balanced XLR
Gender: Male
Contacts: 3-pin

Dimensions/Weight

 Length:
 165mm

 Diameter:
 54mm

 Net Weight:
 453 g (16 oz)

INCLUDED ACCESSORIES

Stand Adapter





